

5148 PRIMER



U.P Code
pw-G-dwv-sw

PRODUCT DATA SHEET

DESCRIPTION

5148 is a solvent primer for priming PVC and CPVC plastic pipe and fittings. Tests have shown that greater long-term joint strength is obtained with the use of a primer. Primer cleans, softens and dissolves the surface of the pipe and fitting, thus providing better bonding surfaces for the solvent cement when it is applied. 5148 meets 'LOW-VOC' requirements, as outlined by SCAQMD 1168/316A.

APPLICATION

5148 Primer is recommended for pressure applications. Additional applications include potable water, DWV (drain, waste, vent), conduit, irrigation and sewer systems.

5148 is manufactured to the high standard of ASTM F 656 to ensure a quality product. A sample is kept from each batch to verify the quality of US Weld products.

Follow the directions on can label. Additional information is available upon request. Skill and knowledge on the part of the user is required to make a good quality joint.

SAFETY PRECAUTIONS

EXTREMELY FLAMMABLE. Do not use or store near heat, sparks or flame. Use only in well-ventilated area. Keep container closed when not in use. Avoid prolonged breathing of vapor. Avoid contact with skin and eyes. In case of skin or eye contact, flush repeatedly with water. Get medical attention if irritation persists. If swallowed, drink water, do NOT induce vomiting and call a physician. Keep out of reach of children





TECHNICAL DATA

Product	Viscosity	Color	Density
5148	Water- thin	Clear /{urple	7.1 lb/gal

MAX VOC PER SCAQMD 1168/316A	550 G/L
SPECIFICATIONS	ASTM F 656, SCAQMD 1168/316
FLASH POINT	6° F (closed cup)
SHELF LIFE	2 year minimum
LISTINGS	NSF (National Sanitation Foundation) U.P. Code (Uniform Plumbing Code)

PACKAGING

Size	Size in Oz	Size in Ml	Units/Case	Cases/Pallet (20' container)	Cases/Pallet (40' container)
¼ Pt.	4	118	24	200	320
½ Pt.	8	237	24	117	182
Pint	16	473	12	128	192
Quart	32	946	12	70	100